



(12) **United States Patent**
King et al.

(10) **Patent No.:** US 7,854,310 B2
 (45) **Date of Patent:** Dec. 21, 2010

(54) **PARKING METER**

(75) Inventors: **David William King**, San Diego, CA (US); **Murray David Kirby Hunter**, Balmain (AU); **Mathew James Hall**, Balmain (AU); **David Andrew Jones**, Balmain (AU)

(73) Assignee: **IPS Group, Inc.**, San Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 113 days.

(21) Appl. No.: **12/072,524**

(22) Filed: **Feb. 27, 2008**

(65) **Prior Publication Data**

US 2008/0245638 A1 Oct. 9, 2008

(30) **Foreign Application Priority Data**

Feb. 27, 2007 (AU) 2007900999

(51) **Int. Cl.**

G07F 9/10 (2006.01)

(52) **U.S. Cl.** **194/350**

(58) **Field of Classification Search** 194/350
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,161,046 A *	6/1939	Hitzeman	194/205
4,880,097 A	11/1989	Speas		
5,222,076 A	6/1993	Ng et al.		
5,563,491 A	10/1996	Tseng		
5,614,892 A	3/1997	Ward, II et al.		
5,659,306 A	8/1997	Bahar		

5,841,369 A	11/1998	Sutton et al.	
5,842,411 A	12/1998	Jacobs et al.	
5,852,411 A	12/1998	Jacobs et al.	
6,111,522 A	8/2000	Hiltz et al.	
6,309,098 B1 *	10/2001	Wong 368/94
6,312,152 B2	11/2001	Dee et al.	
6,457,586 B2 *	10/2002	Yasuda et al. 209/534
2001/0051531 A1	12/2001	Singhal et al.	
2003/0128136 A1	7/2003	Spier et al.	
2006/0152349 A1	7/2006	Ratnakar	
2008/0071611 A1 *	3/2008	Lovett 705/13
2008/0238715 A1	10/2008	Cheng et al.	

FOREIGN PATENT DOCUMENTS

EP **0980055 B1** 2/2000

OTHER PUBLICATIONS

(Cell Net Data Systems) "First Wireless Monitoring of Parking Meters Results in Theft Arrests Using CellNet Data Systems Technology," PRNewswire, May 11, 1999, 2 pages.

* cited by examiner

Primary Examiner—Stefanos Karmis


Assistant Examiner—Mark J Beauchaine


(74) *Attorney, Agent, or Firm*—Townsend and Townsend and Crew LLP

(57) **ABSTRACT**

A parking meter assembly (10) including a base (11) that is to be fixed to or embedded in a ground surface, typically adjacent the curb that which a car is to be parked. The assembly (10) also includes a parking meter (13) having a front face (17) that includes a coin slot (25) a card slot (20) and a control panel (21). The parking meter (13) further includes a rear face (27) having a window aperture (28) that provides for the transmission of light to a solar panel (29) behind the aperture (28).

11 Claims, 5 Drawing Sheets










Fig 2

13
Fig 3





1

PARKING METER

TECHNICAL FIELD

The present invention relates to parking meters and more particularly to electrically powered parking meters. 5

BACKGROUND OF THE INVENTION

Parking meters initially were coin operated. They were known to consist of a module to be fixed to a post having a lower end embedded in a ground surface typically adjacent a kerb adjacent which vehicles were to be parked. The parking meters were operated by inserting a coin and then turning a knob to activate a "clock" mechanism. When a certain period had expired, the parking meter would display a sign indicating the parking period had expired. 10 15

The abovementioned parking meters had a number of disadvantages including complexity of the working mechanisms, unreliability in respect of coins jamming and not being well adapted to provide a range of parking times and costs in respect thereof. A still further advantage is that were restricted to coin operation. 20

OBJECT OF THE INVENTION

It is the object of the present invention to overcome or substantially ameliorate at least one of the above disadvantages.

SUMMARY OF THE INVENTION

There is disclosed herein a parking meter including:

- a coin sensor;
- a card reader;
- an electronic device electrically connected to the sensor and reader so as to receive information electronically therefrom, a display to provide information visually, a telephone connection to provide receiving information in respect of a card used in respect of said card reader, and connections for at least one rechargeable battery to power the reader, sensor and device; and 40
- a solar cell operatively associated with said connections to charge said battery;
- a body having;
- a front face having a coin slot into which coins are inserted for delivery to the sensor and then the coin storage facility;
- a card slot into which a card is inserted to be read by said reader, and a rear face providing a window via which said solar cell is exposed to light, and providing visual access to said display. 50

Preferably, said meter includes an indicator to provide an indication whether a parking period has expired.

Preferably, said indicator is adjacent or at said rear face.

Preferably, said meter is adapted to be fixed to a post fixed to a ground surface, with said body including a set of panels to be fixed relative to said post, and a cover panel pivotally attached to the panel set for pivoting movement about a generally horizontal axis between a closed position and an open position. 55

Preferably, said meter includes controls at said front face via which a user can operate the parking meter.

Preferably, said coin sensor, said card reader, said device and said control panel are a module removable as an assembly from within said body. 60

Preferably, said module includes a body, and said coin sensor is a coin validator unit removably located in said body.

2

Preferably, said telephone is a mobile (cellular) telephone. Preferably, said front face and rear face converge upwardly.

BRIEF DESCRIPTION OF THE DRAWINGS

A preferred form of the present invention will now be described by way of example with reference to the accompanying drawings wherein:

FIG. 1 is a schematic isometric view of a parking meter assembly;

FIG. 2 is a schematic front isometric view of a parking meter employed in the assembly of FIG. 1;

FIG. 3 is a schematic rear isometric view of the parking meter of FIG. 2;

FIG. 4 is a schematic front isometric view of the parking meter of FIG. 2 with a top panel pivoted to an open position; and

FIG. 5 is a schematic rear isometric view of a module of the parking meter of FIG. 2.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

In the accompanying drawings there is schematically depicted a parking meter assembly **10**. The assembly **10** includes a base **11** that would be fixed to or embedded in a ground surface, typically adjacent the kerb at which a car is to be parked. Attached to the base and extending upwardly therefrom is a post **12** to the upper end of which there is attached a parking meter **13**. The parking meter **13** includes a lower skirt **14** that is to be fixed to the post **12**, an intermediate panel set **15**, and a cover panel **16** pivotally mounted relative to the panel set **15**. The cover panel **16** and panel set **15** provide a front face **17** having front face portions **18** and **19**. The front face **17** includes a coin slot **25**, a card slot **20** and a control panel **21**. The control panel **21** includes a window **22**, and buttons **24** that are manipulated by a user to operate the parking meter **13**. The window **22** provides a user with means of viewing a screen **23** via which information is conveyed to the user. The information typically would include date, time and when the parking period is to expire and perhaps further information such as when the parking meter **13** is operable, information in respect of card use and cost. 25 30 35 40

The cover panel **16** is pivotally attached to the panel set **15** by means of a pivot **26** providing a generally horizontal pivot axis **45** that is generally normal to the post **12**. The cover panel **16** is pivotally movable through an acute angle from the closed position as shown in FIGS. 1 and 2, to the open position shown in FIG. 4. In an alternative form, the panel **16** may be slidably attached. 45 50

The rear of the parking meter **13** includes a rear face **27** as part of the cover panel **16**. The rear face **27** includes a window aperture **28** that receives a panel that provides for the transmission of light to a solar panel **29**. The front face portion **18** and rear face **27** converge upwardly so that they are both inclined by acute angles to the horizontal.

At or adjacent the rear face **27** is an indicator **30** that can be viewed easily by a parking ranger moving past the meter **10**, the indicator **30** providing an indication in respect of whether a parking period has expired. 55 60

When mounted adjacent a kerb separating a footpath from a roadway, the rear face **27** would face the adjacent roadway and the front face **17** away from the roadway so that a user would be standing on the footpath and facing their vehicle when operating the meter **13**.

The panel set **15** and cover panel **16** provide a housing **31** within which a module **32** is located. The module **32** includes

an electronic device **33** that incorporates the screen **23**. The module **32** particularly includes a coin sensor **34** in the form of a coin validator **35**. The coin validator **35** is received within a slot **37** of the body **36** of the module **32**. Typically the coin validator **35** would provide a passage **37** through which coins would move to be “counted” and validated for the purposes of the coin validator **35** providing a signal in respect of whether appropriate coins have been delivered to the slot **25**. Accordingly, the passage **37** would communicate with the slot **25** so as to receive coins therefrom. Once passing through the coin validator **35**, the coins are delivered to a coin receptacle than can be cleared. The coin receptacle is located behind the skirt **14** which preferably has a door to provide for access to the coin receptacle. The coin validator **35** is provided as a unit and is removable from the module **32**, when the module **32** is removed from within the housing **31**.

The module **32** is also provided with a light (LED) **38** and/or colour disk **39** that are operated to provide an indication in respect of whether a parking period has expired. The light **38** and/or disk **39** are part of the indicator **30** and can be seen by the parking ranger. Typically the disk **39** would be pivotally mounted and would be “flipped” to be black or red, the red indicating that a parking period has expired.

Located immediately behind the slot **20** is a card reader **40** that would read the magnetic strip (or other information providing device) on a credit or debit card.

The coin validator **35** and card reader **40** are electrically linked to the control panel **21** to provide information therefor in respect of whether payment has been made.

Preferably, the device **33** would include a mobile (cellular) phone link so that information may be conveyed and received in respect of a credit or debit card read by the card reader **40**. The device **33** may also include a power supply (battery), an IR port and LED status indicators.

Preferably, the slot **20** is located in a plane that is inclined to the horizontal by an acute angle so that the slot **20** slopes downwardly to an inclined surface **41** being part of the front face **17**. The surface **41** is downwardly facing so as to protect the slot **20** from water penetration. The surface **41** is also provided with a recess **42** enabling a user’s fingers to hold the card while “swiping” card through the slot **20**.

A key operated lock **43** is located in a rear panel **44** of the panel set **15**, the lock **43** being operable to release the cover panel **16** when appropriate key is used.

The invention claimed is:

1. A parking meter including:

a coin sensor;

a card reader;

an electronic device electrically connected to the sensor and reader so as to receive information electronically therefrom, the electronic device having a screen to provide information visually, a telephone connection to provide receiving information in respect of a card used in respect of said card reader, and connections for at least one rechargeable battery to power the reader, sensor and device;

a solar cell operatively associated with said connections to charge said battery;

a housing in which the coin sensor, card reader, and electronic device are located, the housing comprising an intermediate panel set and a cover panel, wherein the cover panel is movably attached to the intermediate panel set, and a surface of the cover panel and a surface of the intermediate panel set comprise a front face, and the front face surface of the cover panel includes a control panel having a window and a plurality of buttons that operate the parking meter upon manipulation by a user;

a coin slot in the front face into which coins are inserted for delivery to the sensor and then to a coin receptacle;
a card slot in the front face into which a card is inserted to be read by said reader;

a rear face comprising a surface of the cover panel and a surface of the intermediate panel set providing a window aperture via which said solar cell is exposed to light; wherein the coin sensor and the card reader are electrically linked to provide information to the electronic device to provide information of whether payment has been made; wherein the screen of the electronic device is visible through the window of the control panel when the cover panel is attached to the intermediate panel.

2. The parking meter of claim 1, wherein said meter includes an indicator to provide an indication whether a parking period has expired.

3. The parking meter of claim 2, wherein said indicator is adjacent or at said rear face.

4. The parking meter of claim 1, wherein said meter is adapted to be fixed to a post fixed to a ground surface, with said intermediate panel set including a set of panels to be fixed relative to said post, and the cover panel is pivotally attached to the intermediate panel set for pivoting movement about a generally horizontal axis between a closed position and an open position.

5. The parking meter of claim 1, wherein said coin sensor, said card reader, said electronic device and said screen are a module removable as an assembly from within said housing.

6. The parking meter of claim 5, wherein said module includes a body, and said coin sensor is a coin validator unit removably located in said body.

7. The parking meter of claim 1, wherein said telephone connection is a mobile (cellular) telephone connection.

8. The parking meter of claim 1, wherein said front face and rear face converge upwardly.

9. A parking meter comprising:

a housing comprising an intermediate panel set and a cover panel, the cover panel being movably attached to the intermediate panel set, wherein a first surface of the cover panel and a first surface of the intermediate panel set comprise a parking meter front face, the first surface of the cover panel having a first window and a plurality of buttons that operate the parking meter upon manipulation by a user, wherein a second surface of the cover panel and a second surface of the intermediate panel set comprise a parking meter rear face, the rear face surface of the cover panel providing a second window;

a module configured to be removably received by the housing, the module comprising

(a) a coin sensor,

(b) a card reader, and

(c) an electronic device electrically connected to the sensor and the reader so as to receive information electronically therefrom, the electronic device comprising

(i) a screen to provide information visually via the first window when the cover panel is attached to the intermediate panel set,

(ii) a telephone connection to provide receiving information in respect of the card reader,

(iii) a rechargeable battery electrically coupled to provide power to the reader, the sensor, and the electronic device, and

(iv) a solar cell operatively coupled with the rechargeable battery to charge the rechargeable battery, the solar cell being disposed to receive light via the second window;

5

a coin slot in the parking meter front face into which coins are inserted for delivery to the coin sensor and then to a coin receptacle; and

a card slot in the parking meter front face into which a card is inserted to be read by the reader;

wherein the coin sensor and the card reader are electrically linked to provide information to the electronic device to provide information of whether payment has been made.

10. The parking meter of claim **9**, wherein said card slot slopes downwardly to be accessible via the front face surface

6

of the intermediate panel, and the front face surface of the intermediate panel is downwardly facing.

11. The parking meter of claim **9**, wherein the coin sensor comprises a coin validator unit that is removably attached to the module and includes the coin receptacle such that the coin sensor communicates with the coin slot of the parking meter front face when attached to the module for receiving inserted coins.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,854,310 B2
APPLICATION NO. : 12/072524
DATED : December 21, 2010
INVENTOR(S) : King et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the claims

Column 4, line 65, please delete "batter" and replace with --battery--

Signed and Sealed this
First Day of December, 2015



Michelle K. Lee
Director of the United States Patent and Trademark Office